. .

CLAIMS
1. (WITHDRAWN) A stable compound having a molecular formula H ₉ O ₄ ⁺ .
2 (WITHDRAWN) A method for causing substantially complete
dissociation of polyprotic acid in water, said method comprising the steps:
(i) subjecting said water to at least one of mechanical agitation and
magnetic perturbation;
(ii) mixing said polyprotic acid in said water whereby an aqueous polyprotic
acid solution is formed;
(iii) adding a compound of calcium to water to form a solution of Ca ²⁺ ions
in water;

- (iv) subjecting an aqueous solution of Ca²⁺ ions to an electric field arranged to convert said Ca²⁺ ions to Ca³⁺ ions whereby a solution of Ca³⁺ ions is generated;
- (v) mixing said solution of Ca³⁺ ions with said aqueous polyprotic solution whereby Ca₂(SO₄)₃ precipitates in a liquid are formed;
- (vi) removing said Ca₂(SO₄)₃precipitates from said liquid leaving a remaining liquid.

- 3 (currently amended) A method for generating $H_9O_4^+$, said method comprising the steps in operable order:
- (i) subjecting water to at least one of mechanical agitation and magnetic perturbation;
- (ii) mixing reagent grade sulfuric acid in said water whereby an aqueous sulfuric acid solution is formed;

- (iii) adding a compound of calcium to water to form a solution of Ca²⁺ ions in water;
- (iv) subjecting an aqueous solution of Ca²⁺ ions to an electric field arranged to convert said Ca²⁺ ions to Ca³⁺ ions whereby a solution of Ca³⁺ ions is generated;
- (v) mixing said solution of Ca³⁺ ions with said aqueous sulfuric acid solution whereby CaSO₄ precipitates in a liquid are formed;
- (vi) removing said CaSO₄ precipitates from said liquid leaving a remaining liquid;
- (vii) lowering temperature of said remaining liquid to where a slush is formed, wherein said slush comprises ice and remaining liquid;
- (viii) passing said slush through a filter whereby said remaining liquid is separated from said ice;

(ix) subjecting said remaining liquid to distillation whereby free water is removed from said remaining liquid leaving a liquid compound having a molecular formula $H_0O_4^+$.

4. (original) The method of claim 3 wherein said step of subjecting said water to magnetic perturbation includes subjecting said water to a field from a monopolar magnet.

5. (original) The method of claim 3 wherein said step of subjecting said water to magnetic perturbation includes subjecting said water to a strong magnetic field gradient.

6. (original) The method of claim 3 wherein said step of subjecting said water to mechanical perturbation includes moving said water through a centrifugal pump.

7. (cancelled)

8 (original) The method of claim 3 wherein said step (iii) includes the step of preparing said aqueous solution of Ca²⁺ ions by mixing a calcium compound in water contained in a non-magnetic mixing tank.

9.(original)The method of claim 8 wherein said calcium compound is selected from a group of compounds which consists of calcium metal turnings, calcium hydrate, calcium oxide, calcium hydroxide, calcium phosphate dibasic, calcium sulfate, calcium carbonate.

10 (original) The method of claim 8 wherein said step of mixing said calcium compound in water contained in said non-magnetic mixing tank includes the step of subjecting said calcium compound in water to a monopolar magnetic field.

11. (previously presented) The method of claim 8 wherein said step of mixing said calcium compound in water contained in said non-magnetic

mixing tank includes the step of subjecting said calcium compound in water to a magnetic field gradient.

12 (previously presented) The method of claim 3 wherein said step (iii) includes the step of chilling said solution of Ca²⁺ ions in water where by solubility of said calcium compound is increased.

"13 (previously presented) The method of claim 3 wherein said step (vi) includes the step of allowing said Ca precipitates to settle after which said precipitates are removed by decanting and filtering said solution from said precipitates.

14 (previously presented) The method of claim 3 wherein said step (vi) of adding an anionic surfactant whereby precipitation and settling of precipitates is aided.

15 (previously presented) The method of claim 13 wherein said filter of step (viii) is a twenty mesh screen and step (viii) further includes:

forcing said decanted precipitates with water through a filter press whereby a cake of calcium sulfate is formed, usable as a soil pH modifier.

16_(previously presnted) The method of claim 3 wherein ice collected from step (vi) is added to step (v) of a next cycle in the method for generating $H_0O_4^+$.

17. (previously presented) The method of claim 3 wherein said step (ix) includes the step of performing distillation in a low temperature low pressure environment.

18_(preciously presented) The method of claim 3 which includes after step (ix), an additional step, (x) being any one of:

providing hydrogen for a liquid fuel cell;

satisfying the electrolyte requirements in a battery; a battery electrolyte wherein the greater redox potential of the H9O4+ presents a greater battery voltage.;

replacing mineral acids in pH adjustments whereby accumulation of anions associated with the mineral acids is avoided;

replacing any one of nitric acid and muriatic acids in pretreating steps in electro- and electroless plating;

applying said H₉O₄ compound in biological processes where non reactive properties with organic tissue are required.